

AD-A127 488

HYDROGEN AND SULFUR FROM HYDROGEN SULFIDE II AMBIENT  
TEMPERATURE ELECTROL. (U) MINNESOTA UNIV MINNEAPOLIS  
DEPT OF MECHANICAL ENGINEERING E A FLETCHER 15 APR 83

1/1


UNCLASSIFIED

TR-2 N00014-82-K-0523

F/G 7/4

NL





MICROCOPY RESOLUTION TEST CHART  
NATIONAL BUREAU OF STANDARDS-1963-A

(12)

OFFICE OF NAVAL RESEARCH

Contract N00014-82-K-0523

TECHNICAL REPORT NO. 2

Hydrogen and Sulfur from Hydrogen Sulfide II.  
Ambient Temperature Electrolysis Using Oxidation  
of Hydrogen Sulfide by Air as the Prime Energy Source

by

Edward A. Fletcher

Prepared for Publication  
in  
Energy

University of Minnesota  
Mechanical Engineering Department  
111 Church Street S. E.  
Minneapolis, MN 55455

April 15, 1983

Reproduction in whole or in part is permitted for  
any purpose of the United States Government

This document has been approved for public release  
and sale; its distribution is unlimited

DTIC  
APR 29 1983  
H

AD A127488

DTIC FILE COPY

83 04 26 139

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER TR-2	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Hydrogen and Sulfur from Hydrogen Sulfide II. Ambient Temperature Electrolysis Using Oxidation of Hydrogen Sulfide by Air as the Prime Energy Source		5. TYPE OF REPORT & PERIOD COVERED Technical Report, Interim July 1, 1982 - Oct. 31, 1984
7. AUTHOR(s) Edward A. Fletcher		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Edward A. Fletcher, Dept. of Mechanical Engng. University of Minnesota, 111 Church St. S. E. Minneapolis, MN 55455		8. CONTRACT OR GRANT NUMBER(s) N00014-82-K-0523
11. CONTROLLING OFFICE NAME AND ADDRESS 612A:BAR Office of Naval Research, Dept. of the Navy 800 North Quincy St., Arlington, VA 22217		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS NR 625-830 NR 359-830X
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) Director, Office of Naval Research Detachment, Chicago 536 South Clark Street, Chicago, IL 60605		12. REPORT DATE April 15, 1983
		13. NUMBER OF PAGES 10
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) This document has been approved for public release and sale; its distribution is unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) To be published in <u>Energy</u>		
18. SUPPLEMENTARY NOTES To be published in <u>Energy</u>		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) electrochemical, electrolysis, hydrogen, hydrogen sulfide		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) <b>ABSTRACT</b> —Hydrogen sulfide recovered from the sweetening of fossil fuels or sought as a mineral for its intrinsic value might be converted, in an electrolytic process which uses atmospheric oxygen, into pipeline pressure hydrogen and sulfur. Such a process may be an alternative to the Claus Process, which recovers only sulfur and uses the hydrogen wastefully. It is also suggested that electrolysis provides a mechanism by which other gaseous products, as well as hydrogen, may be brought to pipeline pressures easily.		

Fletcher 1

HYDROGEN AND SULFUR FROM HYDROGEN SULFIDE II.  
AMBIENT TEMPERATURE ELECTROLYSIS USING OXIDATION OF  
HYDROGEN SULFIDE BY AIR AS THE PRIME ENERGY SOURCE

Edward A. Fletcher

Department of Mechanical Engineering  
University of Minnesota  
111 Church St. S.E.  
Minneapolis, MN 55455, U.S.A.

(Received February 25, 1983)

Abstract. Hydrogen sulfide recovered from the sweetening of fossil fuels or sought as a mineral for its intrinsic value might be converted, in an electrolytic process which uses atmospheric oxygen, into pipeline pressure hydrogen and sulfur. Such a process may be an alternative to the Claus Process, which recovers only sulfur and uses the hydrogen wastefully. It is also suggested that electrolysis provides a mechanism by which other gaseous products, as well as hydrogen, may be brought to pipeline pressures easily.



Accession For	
NTIS GRA&I	
DTIC TAB	
Unannounced	
Justification	
By	
Distribution/	
Availability	
Dist	Avail and Spec

## 1. INTRODUCTION

Hydrogen sulfide, an industrial waste, is recovered in large quantities from the sweetening of fossil fuels. In 1979,  $1.76 \times 10^6$  tons of sulfur were recovered from natural gas, and  $2.31 \times 10^6$  tons were recovered from petroleum in the United States. In Canada,  $6.1 \times 10^6$  tons were recovered,<sup>1</sup> mostly as hydrogen sulfide. Hydrogen sulfide has a moderately high heating value, 16.55 kJ/g if it is burned to sulfur dioxide and liquid water.<sup>2</sup> But its use as a fuel would be wasteful of sulfur as well as being environmentally unacceptable. Nevertheless, it is plentiful in nature; it should not be overlooked as a potentially valuable resource.<sup>†</sup>

The Claus process is now most widely used to dispose of  $H_2S$ . In this process, sulfur is recovered and the hydrogen is oxidized to water to furnish low-grade process heat.<sup>3</sup> The heating value of the hydrogen thus used is, on an annual basis, equivalent to that of  $17 \times 10^6$  bbl of gasoline.<sup>4</sup> Alternatively, it could be used to hydrogenate one million tons of coal to produce  $59 \times 10^6$  bbl of high-grade liquid hydrocarbon fuel, about 3% of the number of barrels of petroleum imported into the U.S. in 1980, or to produce about  $3 \times 10^6$  metric tons of ammonia. If  $H_2S$  were sought as a resource, its contribution could be substantially higher.

In a previous paper,<sup>4</sup> we noted that, although we are most intrigued by the use of solar energy to effect the separation and

---

<sup>†</sup>Jon Noring, presently with the Sandia Livermore Laboratory, first emphasized this fact to the author.

recovery of both  $H_2$  and  $S_x$  as well as the concomitant storage of solar energy. Electrolysis of  $H_2S$  and subsequent use of the resulting  $H_2$  with atmospheric  $O_2$  in a fuel cell to provide electric power for electrolysis is an interesting option which deserves consideration. We describe how the idea might be implemented, point out some interesting ramifications which may have general applicability to other systems, and present the results of some simple calculations.

## 2. THERMODYNAMICS OF IDEAL ELECTROLYTIC AND FUEL CELLS

The emf required to electrolyze a substance in a reversible electrolytic cell, or the emf produced by a chemical reaction which occurs within a reversible fuel cell, is given by the Nernst equation<sup>5</sup>

$$E = \pm \Delta G/nF, \quad (1)$$

where  $E$  is the emf of the cell,  $\Delta G$  is the change in the Gibb's function for the overall reaction which occurs in the cell,  $n$  is the number of moles of electrons transferred in the external circuit during the course of the reaction, and  $F$  is the Faraday constant. The  $+$  sign applies if one is dealing with an electrolysis cell; the  $-$  sign applies if one is dealing with a fuel cell.

The change in Gibb's function of a chemical reaction,

$$\sum a_i M_i = 0, \quad (2)$$

where  $M_i$  is a reactant or product and  $a_i$  is its coefficient in

the chemical equation, is given in good approximation by

$$\Delta G = \Delta G^0 + RT \ln \prod P_i^{a_i}, \quad (3)$$

where  $P_i$  is the fugacity of gaseous species  $i$ , assumed here to be ideal and therefore equal to its pressure and is very nearly 1 for condensed species and set equal to 1 for condensed species in this paper.

### 3. THE IDEALIZED PROCESS


Hydrogen-oxygen fuel cells are well known.<sup>6</sup> A patent,<sup>7</sup> which makes use of electrolysis for the production of  $H_2$  and  $S_x$  from  $H_2S$ , exists. It is easy to imagine a coupling in which  $H_2$  and  $S_x$  are produced from  $H_2S$  in an electrolysis cell, the electric power for which is provided by an  $H_2$ - $O_2$  fuel cell which uses part of the  $H_2$  from the electrolysis cell and atmospheric  $O_2$  as its reactants. It is not difficult to imagine various arrangements of mechanical components by means of which the process might be effected. One intriguing feature of the process is that, once  $H_2S$  has been introduced into the cell at its operating pressure in a suitable electrolyte, electrolysis can supply the work of pumping the  $H_2$  to an arbitrarily high pressure (a pipeline pressure, for example) without the need for a mechanical gas-pumping device of any kind.

The thermodynamics of the reversible process is simple and straightforward. A schematic representation of the process is given in Fig. 1. The temperature for our example is 298.15 K. The

Capital P, P subscript 1, P subscript i



overall reaction, as can be seen by reference to Fig. 1, is



If  $P$  and  $x$  in Eq. (4) are chosen so that  $\Delta G = 0$ ,

$$(1-x)RT \ln P + x\Delta G_{\text{H}_2\text{O}}^0 - 0.5xRT \ln 0.209 - \Delta G_{\text{H}_2\text{S}}^0 = 0. \quad (5)$$

Equation (5) may be used to calculate the fraction of the  $\text{H}_2$  in  $\text{H}_2\text{S}$  which must be used to effect the electrolysis and compress the remaining  $\text{H}_2$  to pressure  $P$  in a reversible device. The results are given in Fig. 2, which shows the fraction of  $\text{H}_2$  which must be used up, as well as that which remains for storage, as a function of the storage pressure. Figure 2 also shows the fraction of the  $\text{H}_2$  which is used solely to perform pump work. It is noteworthy that only a tiny fraction of the  $\text{H}_2$  need be sacrificed to bring the remainder to very high pressures, an observation that suggests that electrolytic pumping may have applicability to a great many processes in which a gaseous product, which is to be produced by electrolysis of a condensed phase, is wanted at a high pressure. It suggests that the often wasteful and inefficient process of compressing large volumes of gases may be replaced by pumping liquids first or by using batch processes in which the the system, originally at low pressure, is quickly brought to a high pressure by evolution of an electrolytically generated gas from a liquid solution, followed by collection of the gas at high pressure.

Fletcher 6

Acknowledgements- I would like to thank the Northern States Power Company and the Office of Naval Research, Contract N00014-82-K-0523 for support, which made some of this work possible.

# REFERENCES


1. R.E. Davenport and O. Kamatari, Chemical Economics Handbook, p. 780.0001A. Stanford Research Institute, Palo Alto, CA (Dec 1979), used with permission.
2. F.D. Rossini, D.D. Wagman, W.H. Evans, S. Levine, and I. Jaffe, Selected Values of Chemical Thermodynamic Properties, Circular 500 of The National Bureau of Standards, for sale by the Superintendent of Documents, Washington, D.C. 20402.
3. J.E. Naber, J.A. Wesselingh, and W. Groenendaal, Energy Technology Handbook, pp.9:328-334, edited by D.M. Considine, McGraw-Hill, New York (1977).
4. J.E. Noring and E.A. Fletcher, Energy 7, 651(1982).
5. G.N. Lewis and M. Randall, Thermodynamics and Free Energy of Chemical Substances, p. 402, McGraw-Hill, New York (1923).
6. B.J. Crowe, NASA SP-5115, Fuel Cells, National Aeronautics and Space Administration, Washington, D.C., 1973 for sale by the Superintendent of Documents, Washington, D.C. 20402.
7. R. Lee, U.S. patent 2,839,381, assigned to the Lee Foundation for Nutritional Research, June 17, 1958.
8. Anon. U.S. Standard Atmosphere, 1962: for sale by the Superintendent of Documents, Washington, D.C. 20402.

## FIGURE CAPTIONS

Fig. 1. Schematic representation of the device. Hydrogen sulfide from a source at 1 atm is introduced into the electrolytic cell, which produces  $H_2$  and  $S_x$  at some higher pressure  $P$ . In practice, the  $H_2S$  might be pumped into the electrolysis cell as a liquid or gas or in solution in an appropriate solvent. For our purpose, it is only necessary to note that it has become available to us at 1 atm and that our analysis need not consider the details of the mechanisms by which the components of the system operate. A fraction  $x$  of the  $H_2$  at pressure  $P$  is fed to the fuel cell, and the rest is stored. Hydrogen at pressure  $P$  and  $O_2$  at  $0.209 \text{ atm}^8$  are the reactants in the fuel cell, which rejects liquid water at 1 atm.

Fig. 2. Variation with storage pressure of the fraction of  $H_2$  consumed, stored, and used to provide the work of compressing that which is stored.

ELECTRICAL WORK



$\text{H}_2\text{S}(\text{g}, 1 \text{ atm}) \rightarrow$

$\text{S}(\text{s})$


$x \text{H}_2(\text{g}, P)$

FUEL  
CELL

$\frac{x}{2} \text{O}_2 \left( \begin{array}{l} \text{from air, g} \\ 0.209 \text{ atm} \end{array} \right) \rightarrow$

$(1-x) \text{H}_2(\text{g}, P)$   
TO STORAGE

$\text{H}_2\text{O}(\text{l})$



**END**

**FILMED**

**6-83**

**DTIC**